



SKY NG NACELLE for basket < 16 m

POWER

**LINE
DETECTOR**

*Detectors of High Voltage electric line
for basket < 16 m*

NETWORK EXPERTISE



**COMPLETE RANGE OF
PRODUCTS AND NEWS ON
www.made-sa.com**

MADE S.A.

167, Impasse de la Garrigue · 83210 La Farlède
Tél. : +33 (0) 494 083 198 · Fax : +33 (0) 494 082 879
contact@made-sa.com

In order to improve their equipments, MADE is reserving its rights to modify the products described in that documentation, at any time and without prior notification. © No part of this work may be reproduced and distributed without MADEs prior written permission.

**MADE IN
FRANCE**



● SKY NG NACELLE for basket < 16 m

Detectors of High Voltage electric line for basket < 16 m



SKY NG NACELLE is a detector of high voltage lines : MV (< 50 kV) and HV (> 50 kV). SKY NG NACELLE warns the user with an acoustic and visual signal when the lifting device enters a danger zone at a distance between 3 and 6 m of a high voltage line.

➤ PRESENTATION

SKY NG NACELLE works on the principle of proximity detection with several sensors (3 or 4), for the baskets < 16 m which communicate permanently with the central unit placed in the basket. The communication between the CU and the sensors is wired. A box of visualization and acknowledgment of the signal is placed in the basket. The temporary blockade of the movements can also be proposed (dry contact available).

➤ OPERATION

SKY NG NACELLE starts when the basket starts.

The detection of the electric field turns on the acoustic and visual alarm and provokes the blockade of the movement (with effective cabling).

The driver can turn off the acoustic alarm and the movement blockade (if effective) for a duration of 20 minutes by pushing the button “call-back mode”. The light remains active. A sound alert will then be emitted regularly (every 30 seconds) to indicate the danger. After 20 minutes, the system resets.

➤ TECHNICAL CHARACTERISTICS

- ✓ For a multi-sensors configuration, the configurable detection threshold upon installation varies from 3 to 6 m (10 to 17 feet) from a high voltage line
- ✓ Measurement precision : ± 1 m (3 feet) while moving, with a speed of 1 m/s (3.3 feet/s)
- ✓ Power supply : 24 VDC or 12 VDC
- ✓ Dimensions : 112 x 60 x 30 mm (cabled sensor), 145 x 85 x 90 mm (CU) and 120 x 80 x 70 mm (outside box of visualization)
- ✓ Waterproof standard : IP65
- ✓ Temperature range : -20 °C to +60 °C
- ✓ Self-test system at each power-on
- ✓ The sensibility limits of the device does not allow to detect 230 V to 380 V power lines

